



MXU 550i

EPS



FLAT DEEP GREEN



MOUNTAIN GRAY



The MXU 550i EPS is an energetic and accomplished ATV. It comes with a high level of standard equipment including power steering, a winch and 2" hitch receiver, digital instrument panel, independent front and rear suspension, and front and rear luggage racks. With excellent ergonomics and a vigorous motor, the MXU 550i EPS is ready to work and play.

Special Features: Front and rear cargo racks/2500 lbs. winch

- Class G compliant for ages 16 and up
- Fuel injected 501cc DOHC 4-stroke, 4-valve, single cylinder liquid cooled engine
- CVT automatic transmission with low, high, neutral and reverse gears with park function and engine braking
- Durable 4-wheel independent suspension for sure-footed handling in rough terrain
- On-demand 2WD/4WD with differential lock and shaft drive
- Linked hydraulic disk brakes with park locking feature
- 5-position preload adjustable shocks
- Dual low-and-high beam headlights with LED markers and dual rear brake lights
- USB charging port
- Built-in storage compartments in each front fender and center console
- Relocated fuel cell for improved weight distribution and stability

Instrumentation: Back-Lit Speedometer, Odometer, Tachometer, Fuel Gauge, Gear Position Indicator, Clock, Fault Code Indicator and 2WD/4WD Indicator.



2" RECEIVER HITCH



PRELOAD ADJUSTABLE SHOCKS



LOW-AND-HIGH BEAM HEADLIGHTS



FRONT & REAR CARGO RACKS



2500 LBS. WINCH



PARK FUNCTION & ENGINE BRAKING

MXU 550i EPS SPECIFICATIONS

ENGINE	
ENGINE TYPE	DOHC 4-Stroke, 4-Valve, Fuel Injected Single Cylinder
DISPLACEMENT	501cc
BORE X STROKE	92.75.4mm
CLAIMED HORSEPOWER	33.5hp @ 6500 rpm
CLAIMED TORQUE	28.6ft lbs. @ 5500 rpm
FUEL MANAGEMENT SYSTEM	Electronic Fuel Injection
COOLING SYSTEM	Liquid
IGNITION	Electric
DRIVE TRAIN/BRAKES	
TRANSMISSION	CVT Automatic H-L-N-R-P with Engine Braking
FINAL DRIVE	Push Button On-Demand 2WD/4WD with Differential Lock
FRONT BRAKE	Linked Hydraulic Dual Disk
REAR BRAKE	Linked Hydraulic Disk
CHASSIS/SUSPENSION	
FRONT SUSPENSION/TRAVEL	Independent Dual A-Arm/6.9"
REAR SUSPENSION/TRAVEL	Independent Dual A-Arm/7.3"
FRAME	Pipe Under Bone
FRONT TIRES	25x8-12
REAR TIRES	25x10-12
SHOCKS	5-Position Adjustable Oil Dampened Shocks
TOWING CAPACITY	941 lbs.
WINCH	2500 lbs. winch
RECIEVER HITCH	2"
DIMENSIONS/WEIGHT	
LENGTH	87"
WIDTH	48"
HEIGHT	49.4"
WHEELBASE	51.1"
GROUND CLEARANCE	10.4"
CLAIMED DRY WEIGHT	725.3 lbs.
FUEL CAPACITY	4.36 gal
INSTRUMENTATION	Multi-Function Digital Instrument Display
WARRANTY	
WARRANTY	1-Year Limited Factory Warranty

