

MXU 700i LE

EPS EURO







The MXU 700i LE EPS EURO is an impressive upgrade from the feature-rich MXU 700i EURO. Electric Power Steering (EPS) improves driver maneuverability making it easy to tackle the most challenging terrain. Ground clearance and handling enhanced by our 14-inch alloy wheels with 26-inch tires. Newly added safety features in the Euro Series include an extra-safe combined braking system and anti-theft steering lock to protect the rider and their belongings.

- · Class G compliant for ages 16 and up
- Fuel injected 695cc SOHC 4-stroke, 4-valve, single cylinder liquid cooled engine
- CVT automatic transmission with low, high, neutral and reverse gears and engine braking
- Durable 4-wheel independent suspension for sure-footed handling in rough terrain
- On-demand 2WD/4WD with differential lock and shaft drive
- · Hydraulic disk brakes with park locking feature
- Dual low-and-high beam headlights with LED markers and dual rear brake/taillights
- · USB charging port
- Built-in storage compartments in each front fender and center console
- · Relocated fuel cell for improved weight distribution and stability
- Front and rear cargo racks
- 2" receiver for mounting a standard trailer hitch
- Factory-installed winch
- 965 lbs. towing capacity

Instrumentation: Back-Lit Speedometer, Tachometer, Odometer or Trip Meter, Gear Position Indicator, Fuel Gauge, 2WD/4WD with Differential Lock Indicator, Voltage Indicator and Clock. Additional indicators include High Beam, Fault Code, Brake Fluid, EPS, Hand Brake and High-Temperature Gauge.





965 LBS. TOWING CAPACITY



BEAM HEADLIGHTS

MXU 700i LE EPS EURO

SPECIFICATIONS

	ENGINE
ENGINE TYPE	SOHC 4-Stroke, 4-Valve, Fuel Injected Single Cylinder
DISPLACEMENT	695cc
BORE X STROKE	102x85mm
CLAIMED HORSEPOWER	44.4hp @ 6500 rpm
CLAIMED TORQUE	40.3ft lbs. @ 5500 rpm
FUEL MANAGEMENT SYSTEM	Electronic Fuel Injection
COOLING SYSTEM	Liquid
IGNITION	Electric
	DRIVE TRAIN/BRAKES
TRANSMISSION	CVT Automatic H-L-N-R-P with Engine Braking
FINAL DRIVE	Push Button On-Demand 2WD/4WD with Differential Lock
FRONT BRAKE	Hydraulic Dual Disk
REAR BRAKE	Shaft Mounted Hydraulic Disk
	CHASSIS/SUSPENSION
FRONT SUSPENSION/TRAVEL	Independent Dual A-Arm/6.9"
REAR SUSPENSION/TRAVEL	Independent Dual A-Arm/7.4" with Sway Bar
FRAME	Pipe Under Bone
FRONT TIRES	25x8-14
REAR TIRES	25x10-14
SHOCKS	5-Position Adjustable Oil Dampened Shocks
TOWING CAPACITY	1029 lbs.
WINCH	2500 lbs. winch
RECIEVER HITCH	2"
	DIMENSIONS/WEIGHT
LENGTH	84.2"
WIDTH	49"
HEIGHT	49.2"
WHEELBASE	51.1"
GROUND CLEARANCE	10.7"
CLAIMED DRY WEIGHT	800.3 lbs.
FUEL CAPACITY	5.55 gal
INSTRUMENTATION	Multi-Function Digital Instrument Display
	WARRANTE !
	WARRANTY